



Product Item Numbers



**6.4 Schluter®-DITRA-HEAT** Uncoupling and waterproofing membrane

Item No.	Item	Dimensions
DH5 12M	Roll	3' 3" x 41' 1" = 134.5 ft <sup>2</sup> (1 m x 12.5 m = 12.5 m <sup>2</sup> )
DH5 MA	Sheet	3' 3" x 2' 7" = 8.6 ft <sup>2</sup> (1 m x 0.8 m = 0.8 m <sup>2</sup> )

U.S. Pat. No. 8,950,141, and U.S. DES. PAT. No. D706459  
 Canada © Schluter Systems L.P. and other patents pending.



**6.4 Schluter®-DITRA-HEAT-DUO** Uncoupling and waterproofing membrane with integrated sound control and thermal break

Item No.	Item	Dimensions
DHD 810 M	Roll	3' 3" x 33' = 108 ft <sup>2</sup> (1 m x 10 m = 10 m <sup>2</sup> )
DHD 8 MA	Sheet	3' 3" x 2' 7" = 8.6 ft <sup>2</sup> (1 m x 0.8 m = 0.8 m <sup>2</sup> )

Patent pending



**6.4 Schluter®-DITRA-HEAT-E-HK** Heating cable

Item No.	Heating Cable Length		Area Covered per Cable Spacing				Total Power (W)	Avg. Power per Unit Area per Cable Spacing				Current (Amps)
			Regular 3 Stud		Alternating 3-2 Stud			Regular 3 Stud		Alternating 3-2 Stud		
	(ft)	(m)	(ft <sup>2</sup> )	(m <sup>2</sup> )	(ft <sup>2</sup> )	(m <sup>2</sup> )		(Watts/ft <sup>2</sup> )	(Watts/m <sup>2</sup> )	(Watts/ft <sup>2</sup> )	(Watts/m <sup>2</sup> )	
<b>Heating Cable (120 V)</b>												
DHE HK 120 11	35.3	10.8	10.7	1.0	8.9	0.8	135	12.6	136	15.2	164	1.1
DHE HK 120 16	52.9	16.1	16.0	1.5	13.3	1.2	203	12.7	136	15.2	164	1.7
DHE HK 120 21	70.5	21.5	21.3	2.0	17.8	1.7	270	12.7	136	15.2	164	2.3
DHE HK 120 27	88.2	26.9	26.7	2.5	22.2	2.1	338	12.7	136	15.2	164	2.8
DHE HK 120 32	105.8	32.2	32.0	3.0	26.7	2.5	405	12.7	136	15.2	164	3.4
DHE HK 120 38	124.1	37.8	37.5	3.5	31.3	2.9	475	12.7	136	15.2	164	4.0
DHE HK 120 43	141.1	43.0	42.7	4.0	35.6	3.3	540	12.7	136	15.2	164	4.5
DHE HK 120 51	169.8	51.8	51.4	4.8	42.8	4.0	650	12.7	136	15.2	164	5.4
DHE HK 120 64	212.9	64.9	64.4	6.0	53.7	5.0	815	12.7	136	15.2	164	6.8
DHE HK 120 73	240.2	73.2	72.7	6.8	60.6	5.6	920	12.7	136	15.2	164	7.7
DHE HK 120 83	275.5	84.0	83.3	7.7	69.4	6.5	1055	12.7	136	15.2	164	8.8
DHE HK 120 92	303.0	92.4	91.7	8.5	76.4	7.1	1160	12.7	136	15.2	164	9.7
DHE HK 120 102	336.9	102.7	101.9	9.5	84.9	7.9	1290	12.7	136	15.2	164	10.7
DHE HK 120 113	372.2	113.4	112.6	10.5	93.8	8.7	1425	12.7	136	15.2	164	11.9
DHE HK 120 134	444.0	135.3	134.3	12.5	111.9	10.4	1700	12.7	136	15.2	164	14.2
<b>Heating Cable (240 V)</b>												
DHE HK 240 11	35.3	10.8	10.7	1.0	8.9	0.8	135	12.6	136	15.2	164	0.6
DHE HK 240 16	53.1	16.2	16.1	1.5	13.4	1.2	203	12.6	136	15.2	164	0.8
DHE HK 240 21	70.6	21.5	21.4	2.0	17.8	1.7	270	12.7	136	15.2	164	1.1
DHE HK 240 27	88.2	26.9	26.7	2.5	22.2	2.1	338	12.7	136	15.2	164	1.4
DHE HK 240 32	105.8	32.2	32.0	3.0	26.7	2.5	405	12.7	136	15.2	164	1.7
DHE HK 240 38	124.1	37.8	37.5	3.5	31.3	2.9	475	12.7	136	15.2	164	2.0
DHE HK 240 43	141.0	43.0	42.6	4.0	35.5	3.3	540	12.7	136	15.2	164	2.3
DHE HK 240 53	176.3	53.7	53.3	5.0	44.4	4.1	675	12.7	136	15.2	164	2.8
DHE HK 240 64	211.6	64.5	64.0	5.9	53.3	5.0	810	12.7	136	15.2	164	3.4
DHE HK 240 75	248.2	75.7	75.1	7.0	62.6	5.8	950	12.7	136	15.2	164	4.0
DHE HK 240 85	282.1	86.0	85.3	7.9	71.1	6.6	1080	12.7	136	15.2	164	4.5
DHE HK 240 103	339.4	103.4	102.7	9.5	85.6	7.9	1300	12.7	136	15.2	164	5.4
DHE HK 240 129	425.8	129.8	128.8	12.0	107.3	10.0	1630	12.7	136	15.2	164	6.8
DHE HK 240 145	480.5	146.5	145.3	13.5	121.1	11.3	1840	12.7	136	15.2	164	7.7
DHE HK 240 167	551.0	167.9	166.7	15.5	138.9	12.9	2110	12.7	136	15.2	164	8.8
DHE HK 240 183	605.9	184.7	183.3	17.0	152.7	14.2	2320	12.7	136	15.2	164	9.7
DHE HK 240 204	673.8	205.4	203.8	18.9	169.9	15.8	2580	12.7	136	15.2	164	10.7
DHE HK 240 225	744.4	226.9	225.2	20.9	187.7	17.4	2850	12.7	136	15.2	164	11.9



**6.4 Schluter®-DITRA-HEAT-E-WiFi** Digital thermostat

Item No.	Description
DHE RT 104/BW	Programmable Wi-Fi thermostat with floor temperature sensor in bright white



according to the following standards: UL 60730-1, UL 60730-2-9, CSA E60730-1, CSA E60730-2-9, UL E-file: E157297, GFCI: UL 943 4th ed., CSA C22.2 No. 144.1-06



**6.4 Schluter®-DITRA-HEAT-E-RT** Digital thermostat

Item No.	Description
DHE RT 102/BW	Touchscreen programmable thermostat with floor temperature sensor in bright white



according to the following standards: UL 60730-1, UL 60730-2-9, CSA E60730-1, CSA E60730-2-9, UL E-file: E157297, GFCI: UL 943 4th ed., CSA C22.2 No. 144.1-06



**6.4 Schluter®-DITRA-HEAT-E-R** Digital thermostat

Item No.	Description
DHE RT 103/BW	Non-programmable thermostat with floor temperature sensor in bright white

according to the following standards: UL 60730, CSA E60730-1, UL E-file: E157297, GFCI: UL 943, CSA C22.2 No.144.1-06



**6.4 Schluter®-DITRA-HEAT-E-RSD** Digital thermostat

Item No.	Description
DHE RSD/BW	Programmable thermostat with floor temperature sensor in bright white

Listed by C ETL us



**6.4 Schluter®-DITRA-HEAT-E-RR** Power module


Item No.	Description
DHE RR 1/BW	Power module

according to the following standards: CSA E60730-1, GFCI: UL 943, CSA C22.2 No.144.1-06



**6.4 Schluter®-DITRA-HEAT-E-KIT** Wi-Fi touchscreen programmable thermostat

<b>Item No.</b>	DHE K RT W 120 40	DHE K RT W 120 56
<b>Matting</b>	5 sheets – 43.1 ft <sup>2</sup> (4.0 m <sup>2</sup> )	7 sheets – 60.3 ft <sup>2</sup> (5.6 m <sup>2</sup> )
<b>Heating cable</b>	88' 3" – 26.7 ft <sup>2</sup> (26.9 m – 2.5 m <sup>2</sup> )	124' 0" - 37.5 ft <sup>2</sup> (37.8 m - 3.5 m <sup>2</sup> )
<b>Thermostat</b>	1 – white, Wi-Fi touchscreen programmable	1 – white, Wi-Fi touchscreen programmable



**6.4 Schluter®-DITRA-HEAT-E-KIT** Touchscreen programmable thermostat

<b>Item No.</b>	DHE K RT 120 40	DHE K RT 120 56
<b>Matting</b>	5 sheets – 43.1 ft <sup>2</sup> (4.0 m <sup>2</sup> )	7 sheets – 60.3 ft <sup>2</sup> (5.6 m <sup>2</sup> )
<b>Heating cable</b>	88' 3" – 26.7 ft <sup>2</sup> (26.9 m – 2.5 m <sup>2</sup> )	124' 0" - 37.5 ft <sup>2</sup> (37.8 m - 3.5 m <sup>2</sup> )
<b>Thermostat</b>	1 – white, programmable touchscreen	1 – white, programmable touchscreen